



FOR CONTINUOUS USE, LIMIT POWER FACTOR AT PLATE TO 150PF.
RECOMMENDATION IS CALCULATED FOR APPROX 1.5kg PLATE (D150XW10), WHICH IS SETTABLE TO FALL WITH MINIMUM PF 50.

INCREASE PLATE THICKNESS/WEIGHT IF SHORTER SHOOTING DISTANCES OR HIGHER MINIMUM PF ARE REQUIRED.

TPS1 DESIGNED TO BE USED WITH SHOTGUN BIRDSHOT AND FOR TRAINING PURPOSES ONLY.

SUGGESTED MINIMUM SHOOTING DISTANCE WITH 28g LOAD:

CYLINDER	8m
IMPROVED CYLINDER	12m
MODIFIED	15m
FULL	17m

RUBBER BAND DIA 200 WIDTH 10, OR LONGER	1
S-HOOK 6MM	2
WASHER M12 DIN125	4
NYLON INSERT LOCK NUT M12 DIN985	14
SCREW M12x50 DIN931	2
SCREW M12x200 DIN933 FULL THREAD	4
PLATE (FLAT 150x150x10 OR EQV)	1
SQUARE HOLLOW 30x30x3x260	1
FLAT STEEL BAR 30x5x1200	4
Item	pcs
KING-TPS1	



KING
COMPETITION PRODUCTS